Dissolvable Frac Ball

Not your average frac ball.





With over 70 different variations we are able to customize our disintegrating Max-D Frac Ball™to the exact specifications of your wellbore conditions. Given the fluid used, differential pressure and seat size, we can tell you how much pressure the ball will withstand and how long it will take to pass through the seat. The Max-D Frac Ball™ comes in any size needed to do the job. We keep certain sizes on the shelf ready to ship and custom balls can be made and shipped within 48 hours of receiving the order.

applications

FRAC PLUGS AND PACKERS DIVERTER BALLS DRILLING APPLICATIONS HYDRAULIC DISCONNECTS FRAC SLEEVES

standard sizes

0.875 (7/8") 1.00 (1") 1.125 (9/8") 1.250 (5/4") 1.375 (11/8") 1.50 (3/2") 1.625 (13/8") 1.750 (7/4") 1.875 (15/8") 2.000 (2")

2.125 (17/8") 2.250 (9/4") 2.375 (19/8") 2.500 (5/2") 2.625 (21/8") 2.750 (11/4") 2.875 (23/8") 3.000 (3") 3.125 (25/8") 3.250 (13/4") 3.375 (27/8") 3.50 (7/2") 3.625 (29/8") 3.750 (15/4") 3.875 (31/8") 4.000 (4") 4.125 (33/8") 4.250 (18/4") 4.375 (35/8") 4.50 (9/2")

