

<b>X-FACTOR FULLY DISSOLVABLE PLUG</b>				
PLUG TYPE	CASING SIZE INCHES/(mm)	CASING WT lb/ft (Kg)	MAX TEMPERATURE °F	MAX PRESSURE PSI / Mpa
BALL DROP	4.5 (114.3)	11.6 - 15.1 (5.26 - 6.85)	350°F (177°C)	10,000 psi (70)
BRIDGE PLUG	4.5 (114.3)	11.6 - 15.1 (5.26 - 6.85)	350°F (177°C)	10,000 psi (70)
CAGED BALL	4.5 (114.3)	11.6 - 15.1 (5.26 - 6.85)	350°F (177°C)	10,000 psi (70)

<b>X-FACTOR FULLY DISSOLVABLE PLUG</b>				
PLUG TYPE	CASING SIZE INCHES/(mm)	CASING WT lb/ft (Kg)	MAX TEMPERATURE °F	MAX PRESSURE PSI / Mpa
BALL DROP	5.5 (139.7)	20 - 26.8 (9.07 - 12.16)	350°F (177°C)	10,000 psi (70)
BRIDGE PLUG	5.5 (139.7)	21 - 26.8 (9.07 - 12.16)	350°F (177°C)	10,000 psi (70)
CAGED BALL	5.5 (139.7)	22 - 26.8 (9.07 - 12.16)	350°F (177°C)	10,000 psi (70)

<b>VORTEX FAST DRILL PLUG</b>				
PLUG TYPE	CASING SIZE INCHES/(mm)	CASING WT lb/ft (Kg)	MAX TEMPERATURE °F	MAX PRESSURE PSI / Mpa
BALL DROP	4.5 (114.3)	11.6 - 15.1 (5.26 - 6.85)	TYPE A: 250°F (121°C)	12,000 psi (70)
			TYPE B: 350°F (177°C)	
BRIDGE PLUG	4.5 (114.3)	11.6 - 15.1 (5.26 - 6.85)	TYPE A: 250°F (121°C)	12,000 psi (70)
			TYPE B: 350°F (177°C)	
CAGED BALL	4.5 (114.3)	11.6 - 15.1 (5.26 - 6.85)	TYPE A: 250°F (121°C)	12,000 psi (70)
			TYPE B: 350°F (177°C)	

<b>VORTEX FAST DRILL PLUG</b>				
PLUG TYPE	CASING SIZE INCHES/(mm)	CASING WT lb/ft (Kg)	MAX TEMP °F (°C)	MAX PRESSURE PSI / Mpa
BALL DROP	5.5 (139.7)	20 - 26.8 (9.07 - 12.16)	TYPE A: 250°F (121°C)	12,000 psi (70)
			TYPE B: 350°F (177°C)	
BRIDGE PLUG	4.5 (114.3)	21 - 26.8 (9.07 - 12.16)	TYPE A: 250°F (121°C)	12,000 psi (70)
			TYPE B: 350°F (177°C)	
CAGED BALL	4.5 (114.3)	22 - 26.8 (9.07 - 12.16)	TYPE A: 250°F (121°C)	12,000 psi (70)
			TYPE B: 350°F (177°C)	